







Backlit LED Panel 50 W / 605 mm





Surface Backlit Panel Series | Slim LED Panels With electronic control gears










Areas of application

- | | |
|---|--|
|  Homes |  Offices |
|  Stores |  Hotels |
|  Industrials |  stairs and Corridors |

Product benefits

-  Quick, simple and safe replacement without rewiring.
-  Energy savings of up to 65 % (compared to Halogen Spot lamps).
-  Instant-on light, therefore ideally suitable in combination with, sensor technology Very high resistance to switching loads.
-  Also suitable for operation at low and high temperatures.

Product feature

-  Integrated ECG with high power factor
-  Uniform illumination
-  Lifetime: up to 25,000 h
-  Wide beam angle: 120°
-  Mercury-free and RoHS compliant
-  Luminous efficacy: up to 100 lm/W
-  All housing made of Aluminum



Electrical data

Nominal wattage	50.00 W
Rated wattage	50.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal current	0.230 A
Type of current	AC
Power factor λ	> 0.99

Photometrical data

Light color (designation)	Cool White
Rated color temperature	6500 K
Nominal luminous flux	4500 lm
Rated luminous flux	4800 lm
Rated lamp efficacy (standard condition)	90-100 lm/W
Color rendering index Ra	>80
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Warm-up time (60 %)	< 0.5 s
Rated beam angle (half peak value)	120.00 °
Starting time	< 0.5 s

Lifespan

Lifespan	25,000 hrs.
Rated lamp life time	25,000 hrs.
Number of switching cycles	150,000

Certificates & standards

Type of protection	IP 44
Standards	CE
Energy efficiency class	A+
Energy consumption	50 kWh/1000h

Temperatures & operating conditions

Ambient temperature range	-10 +55°C
Maximum temperature at tc test point	65 °C

Capabilities

Dimmable	No
-----------------	----


Logistical Data

Product code	4052899955750
Product description	BL PANEL 6060 - 50W - 6500K
Packaging unit (Pieces/Unit)	1 PCS/Carton
Dimensions (length x width x height)	620 mm x 620 mm x 50 mm
Volume	78.20 cm ³
Gross weight	1564.00 g

Dimensions & weight

Square-Model Mechanical Data

Dimension	605 x 605 (mm)
Height	40
Product weight	1564.00 g



Information furnished is believed to be accurate and reliable. However, TESLA EGYPT assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TESLA EGYPT. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. TESLA EGYPT products are not authorized for use as critical components in life support devices or systems without express written approval of TESLA EGYPT.

The TESLA logo and the green lamp sign is a registered trademark of TESLA EGYPT. All other names are the property of their respective owners.

© 2020 TESLA EGYPT - All rights reserved